

SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's Choice[™] Burmese Wood* -EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Page 1 of 8 Print Date: 2023-03-20

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name: Crafter's Choice™ Burmese Wood* - EO & FO Blend

1.2 Relevant indentified product use

Intended use: Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer: IndiMade Brands, LLC DBA Wholesale Supplies Plus

7820 E Pleasant Valley Road Independence, OH 44131

(800) 359-0944

www.WholesaleSuppliesPlus.com

1.4 Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International

2. Hazards Identification

2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS

Acute Toxicity Oral, Category 4 H302 : Harmful if swallowed

Acute Toxicity Dermal, Category 5 H313 : May be harmful in contact with skin

Skin Corrosion/Irritation, Category 3 H316: Causes mild skin irritation

Sensitization, Skin, Category 1A H317 : May cause an allergic skin reaction

Acute Toxicity Inhalation, Category 5 H333 : May be harmful if inhaled Aquatic Acute Toxicity, Category 1 H400 : Very Toxic to aquatic life

Aquatic Chronic Toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects

Classification OSHA (Provisions 1910.1200 of title 29)

Acute Toxicity Oral, Category 4 H302 : Harmful if swallowed

Sensitization, Skin, Category 1A H317: May cause an allergic skin reaction

Classification Other

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater,

by the following:None [X] ACGIH [] IARC [] NTP [] OSHA []

2.2 Label elements

Labelling (GHS)

Hazard pictograms







SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's ChoiceTM Burmese Wood* EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Page 2 of 8 Print Date: 2023-03-20

Signal Word: Warning

0.9			
Hazard	stater	nents	

H302	Harmful if swallowed
H313	May be harmful in contact with skin
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H400	Very Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention:

sponso:	
P273	Avoid release to the environment
P272	Contaminated work clothing should not be allowed out of the workplace
P270	Do not eat, drink or smoke when using this product
P264	Wash hands thoroughly after handling

Response:

P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse
	mouth
P302 + P352	IF ON SKIN: Wash with soap and water
P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
P333 + P313	If skin irritation or a rash occurs: Get medical advice/attention
P363	Wash contaminated clothing before reuse
P391	Collect Spillage

2.3 Other Hazards

no data available

3. Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

CAS# Ingredient	EC#	Conc. Range	GHS Classification
120-51-4	204-402-9	50 - 60 %	H302; H313; H400; H411
Benzyl Ben	zoate		
1222-05-5	214-946-9	5 - 10 %	H316; H400; H410
Hexamethy	<i>lindanopyran</i>		
66068-84-6	266-100-3	2 - 5 %	H316; H400; H411
Isocamphe	nyl cyclohexanol	(mixed isomers)	
58567-11-6	261-332-1	2 - 5 %	H315; H317; H401; H411
(ethoxymet	hoxy)cyclododed	cane	



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's ChoiceTM Burmese Wood* EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Page 3 of 8 Print Date: 2023-03-20

CAS# Ingredient	EC#	Conc. Range	GHS Classification
77-53-2	201-035-6	2 - 5 %	H401; H411
Cedrol			
18479-58-8	242-362-4	2 - 5 %	H227; H303; H315; H319; H402
2,6-dimeti	hyloct-7-en-2-ol	1	
32388-55-9	251-020-3	2 - 5 %	H303; H317; H400; H410
Acetyl ced	drene		
91-64-5	202-086-7	2 - 5 %	H301; H317; H402
Coumarin			
19870-74-7	243-384-7	1 - 2 %	H317; H400; H410
Cedrol me	ethyl ether		
469-61-4	207-418-4	1 - 2 %	H304; H315; H400; H410
alpha-Ced	drene		
5986-55-0	227-807-2	1 - 2 %	H401; H411
Patchouli	alcohol		
104-55-2	203-213-9	0.1 - 1.0 %	H303; H312; H315; H317; H319; H401;
Cinnamal			H412
97-53-0	202-589-1	0.1 - 1.0 %	H303; H316; H317; H319; H401
Eugenol			
5989-27-5	227-813-5	0.1 - 1.0 %	H226; H304; H315; H317; H400; H412
Limonene			
87-44-5	201-746-1	0.1 - 1.0 %	H304; H317
Beta-Cary	ophyllene –		
See Section 1	6 for full text of	GHS classification	on codes

See Section 16 for full text of GHS classification codes which where not shown in section 2

Total Hydrocarbon Content (% w/w) = 1.75

4. First Aid Measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

Eye Exposure: Flush immediately with water for at least 15 minutes.

Contact physician if symptoms persist.

Skin Exposure: Remove contaminated clothes. Wash thoroughly with water (and soap).

Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's Choice[™] Burmese Wood* - EO & FO Blend

Print Date: 2023-03-20

Page 4 of 8

5. Fire-Fighting measures

5.1 Extinguishing media

www.WholesaleSuppliesPlus.com

7820 E Pleasant Valley Road

Independence, OH 44131 (800) 359-0944

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

UnsuitableDo not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

8. Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits: Contains no substances with occupational exposure limit values.

Engineering Controls: Use local exhaust as needed.

8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's Choice[™] Burmese Wood* EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Page 5 of 8 Print Date: 2023-03-20

Respiratory protection: Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid

Odor: Conforms to Standard

Color: Pale Yellow to Yellow/Golden Yellow (G2-5)

Viscosity: Liquid

Freezing Point:

Boiling Point:

Not determined

Melting Point:

Not determined

Not determined

Not determined

Flashpoint (CCCFP):

>200 F (93.33 C)

Auto flammability:

Not determined

Explosive Properties:

None Expected

Oxidizing properties:

 Vapor Pressure (mmHg@20 C):
 0.0068

 %VOC:
 0.37

 Specific Gravity @ 25 C:
 1.0470

 Density (g/mL) @ 25 C:
 1.0440

 Refractive Index @ 20 C:
 1.5360

 Soluble in:
 Oil

10. Stability and Reactivity

10.1 Reactivity None10.2 Chemical stability Stable

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

10.5 Incompatible materials Strong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition products None known

11. Toxicological Information

11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 1970.9151) Harmful if swallowed

Acute toxicity - Dermal - (Rabbit) mg/kg (LD50: 3152.0914) May be harmful in contact with skin

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LD50: 66.3758) May be harmful if inhaled



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Crafter's Choice[™] Burmese Wood* -Product: EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

Print Date: 2023-03-20

Page 6 of 8

Skin corrosion / irritation Causes mild skin irritation

Serious eye damage / irritation Not classified - the classification criteria are not met Not classified - the classification criteria are not met Respiratory sensitization

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity Not classified - the classification criteria are not met Not classified - the classification criteria are not met Carcinogenicity Reproductive toxicity Not classified - the classification criteria are not met Specific target organ toxicity - single exposure Not classified - the classification criteria are not met Specific target organ toxicity - repeated exposure Not classified - the classification criteria are not met Aspiration hazard

Not classified - the classification criteria are not met

12. **Ecological Information**

12.1 Toxicity

Acute acquatic toxicity Very Toxic to aquatic life

Toxic to aquatic life with long lasting effects Chronic acquatic toxicity

Toxicity Data on soil no data available Toxicity on other organisms no data available

no data available 12.2 Persistence and degradability 12.3 Bioaccumulative potential no data available 12.4 Mobility in soil no data available 12.5 Other adverse effects no data available

13. **Disposal Conditions**

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. **Transport Information**

Marine Pollutant Yes. Ingredient of greatest environmental impact:

120-51-4: (50 - 60 %): Benzyl Benzoate

Regulator Class **Pack Group** Sub Risk UN-nr.

Not Regulated - Not Dangerous Goods U.S. DOT (Non-Bulk)

Chemicals NOI

ADR/RID (International Road/Rail)

Environmentally Hazardous 9 Ш UN3082

Substance, Liquid, n.o.s.

IATA (Air Cargo)



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's ChoiceTM Burmese Wood* -

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com EO & FO Blend

Print Date: 2023-03-20

UN3082

Page 7 of 8

Environmentally Hazardous 9 III

Substance, Liquid, n.o.s. **IMDG (Sea)**

Environmentally Hazardous 9 III UN3082

Substance, Liquid, n.o.s.

15. Regulatory Information

U.S. Federal Regulations

TSCA (Toxic Substance Control Act)

All components of the substance/mixture are listed or exempt

40 CFR(EPCRA, SARA, CERCLA and CAA) This product contains the following components:

1222-05-5 214-946-9 5 - 10 % Hexamethylindanopyran

U.S. State Regulations

California Proposition 65 Warning

This product contains the following components:

140-67-0 205-427-8 0.01 - 0.1% Estragole (Methyl chavicol) (Natural Source)

123-35-3(NF 204-622-5 <= 56 ppm beta-Myrcene (Natural Source)

94-59-7 202-345-4 <= 12 ppm Safrole (Natural Source)

93-15-2 202-223-0 <= 5 ppm Methyl Eugenol (Natural Source)

Canadian Regulations

DSL 100.00% of the components are listed or exempt. The following

components are NOT on the List:

149713-23-5 <= 2 ppm 2H-Pyran, tetrahydro-4-methyl-2-phenyl-,(2R,4S)-rel

16. Other Information

GHS H-Statements referred to under section 3 and not listed in section 2

H226 : Flammable liquid and vapour H227 : Combustible liquid

H301 : Toxic if swallowed
H304 : May be fatal if swallowed and enters airways
H312 : Harmful in contact with skin

H315 : Causes skin irritation H317 : May cause an allergic skin reaction

H319 : Causes serious eye irritation H401 : Toxic to aquatic life

H402 : Harmful to aquatic life H410 : Very toxic to aquatic life with long lasting

effects

H412: Harmful to aquatic life with long lasting effects

Total Fractional Values

(TFV) Risk (TFV) Risk

(76.31) Aquatic Chronic Toxicity, Category 3 (75.33) Acute Toxicity Inhalation, Category 5

(7.63) Aquatic Chronic Toxicity, Category 2 (6.68) Sensitization, Skin, Category 1A (3.25) Aquatic Chronic Toxicity, Category 4 (3.25) Sensitization, Skin, Category 1B

3.25) Aquatic Chronic Toxicity, Category 4 (3.25) Sensitization, Skin, Category 18

(2.90) Aquatic Acute Toxicity, Category 1 (2.07) Skin Corrosion/Irritation, Category 3

(1.59) Acute Toxicity Dermal, Category 5 (1.01) Acute Toxicity Oral, Category 4

Department issuing data sheet:



SDS v1 GHS / OSHA

Revised Date: 2023-02-07 00:00

Product: Crafter's ChoiceTM Burmese Wood* EO & FO Blend

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Page 8 of 8 Print Date: 2023-03-20

Department E-mail address:

Remarks

This safety data sheet is based on the properties of the material known to IndiMade Brands, LLC at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment IndiMade Brands, LLC holds no responsibility. This document is not intended for quality assurance purposes.