

SDS v1 GHS / OSHA

Revised Date: 2023-04-18 00:00

Page 1 of 8 Print Date: 2023-04-27

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Product: Crafter's Choice™ Wood - 100% Upcycled Fragrance Oil

Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name: Crafter's ChoiceTM Wood- 100% Upcycled Fragrance Oil

1.2 Relevant indentified product use

Intended use: Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the safety data sheet

Supplier: IndiMade Brands, LLC DBA Wholesale Supplies Plus

7820 E Pleasant Valley Road Independence, OH 44131

(800) 359-0944

www.WholesaleSuppliesPlus.com

1.4 Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International

2. Hazards Identification

2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS

Flammable Liquids, Category 4 H227 : Combustible liquid

Acute Toxicity Oral, Category 5 H303 : May be harmful if swallowed

Acute Toxicity Dermal, Category 5 H313: May be harmful in contact with skin

Skin Corrosion/Irritation, Category 2 H315 : Causes skin irritation

Sensitization, Skin, Category 1A H317: May cause an allergic skin reaction

Eye Damage/Eye Irritation, Category 1

Acute Toxicity Inhalation, Category 5

H318 : Causes serious eye damage
H333 : May be harmful if inhaled

Aquatic Acute Toxicity, Category 2 H401 : Toxic to aquatic life

Aquatic Chronic Toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects

Classification OSHA (Provisions 1910.1200 of title 29)

Flammable Liquids, Category 4 H227 : Combustible liquid Skin Corrosion/Irritation, Category 2 H315 : Causes skin irritation

Sensitization, Skin, Category 1A H317: May cause an allergic skin reaction

Eye Damage/Eye Irritation, Category 1 H318 : Causes serious eye damage

Reproductive Toxicity, Category 2 H361: Suspected of damaging fertility or the unborn child

Classification Other

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater,

by the following:None [X] ACGIH [] IARC [] NTP [] OSHA []

2.2 Label elements

Labelling (GHS)



SDS v1 GHS / OSHA

Revised Date: 2023-04-18 00:00

Page 2 of 8 Print Date: 2023-04-27

Product: Crafter's Choice™ Wood - 100% Upcycled Fragrance Oil

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

Hazard pictograms







Signal Word: Danger

Hazard statements

H227	Combustible liquid
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H333	May be harmful if inhaled
H361	Suspected of damaging fertility or the unborn child
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention:

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P235	Keep cool
P264	Wash hands thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P273	Avoid release to the environment
P281	Use personal protective equipment as required

Response

sponse:	
P302 + P352	IF ON SKIN: Wash with soap and water
P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses if present and easy to do. continue rinsing
P308 + P313	IF exposed or concerned: Get medical advice/attention
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P333 + P313	If skin irritation or a rash occurs: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P370 + P378	In case of fire: Use Carbon dioxide (CO2), Dry chemical, or Foam for extinction. Do not use a direct water jet on burning material

2.3 Other Hazards

no data available



Product: Crafter's ChoiceTM Wood -

Revised Date: 2023-04-18 00:00

SDS v1 GHS / OSHA

Page 3 of 8 Print Date: 2023-04-27

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

100% Upcycled Fragrance Oil

Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

CAS# Ingredient	EC#	Conc. Range	GHS Classification			
100-79-8	202-888-7	20 - 30 %	H319			
Isopropylio						
78-70-6	201-134-4	10 - 20 %	H227; H303; H315; H317; H319; H402			
Linalool						
106-24-1	203-377-1	10 - 20 %	H303; H315; H317; H318; H402			
Geraniol						
98-55-5	202-680-6	10 - 20 %	H227; H303; H315; H319; H401			
Terpineol						
115-95-7	204-116-4	5 - 10 %	H227; H315; H317; H320; H402			
Linalyl Ace	etate					
236391-76-7	431-700-8	5 - 10 %	H401; H411			
Acetic acid	Acetic acid, (1-oxopropoxy)-, 1-(3,3-dimethylcyclohexyl)ethyl ester					
28219-61-6	248-908-8	5 - 10 %	H315; H319; H401; H411			
Ethyl trime	ethylcyclopentene	e butenol				
18479-58-8	242-362-4	5 - 10 %	H227; H303; H315; H319; H402			
2,6-dimeth	nyloct-7-en-2-ol					
105-87-3	203-341-5	5 - 10 %	H315; H317; H401; H412			
Geranyl A	cetate					
5989-27-5	227-813-5	2 - 5 %	H226; H304; H315; H317; H400; H412			
Limonene						
141-12-8	205-459-2	2 - 5 %	H317; H401			
Neryl acet	ate					
65443-14-3	265-779-3	2 - 5 %	H227; H401; H411			
2,2,5-Trim	ethyl-5-pentylcyd	clopentanone				
4819-67-4	225-392-2	1 - 2 %	H227; H402			
2-Pentylcy	/clopentanone					
2785-87-7	220-499-0	0.1 - 1.0 %	H303; H315; H317; H318; H335; H401			
Dihydroeu	igenol (2-Methox	y-4-propylpheno	<i>I)</i>			
6784-13-0	229-846-0	0.1 - 1.0 %	H317; H412			
3-cyclohex	xene-1-proponal,	beta, 4-dimethy	1			
99-85-4	202-794-6	0.1 - 1.0 %	H226; H303; H304; H316; H361			
gamma-Te	erpinene					
80-56-8	201-291-9	0.1 - 1.0 %	H226; H302; H304; H315; H317; H400;			
pinene			H410			
See Section 1	6 for full text of G	HS classification	n codes			



SDS v1 GHS / OSHA

Revised Date: 2023-04-18 00:00

Product: Crafter's Choice™ Wood - 100% Upcycled Fragrance Oil

Page 4 of 8

Print Date: 2023-04-27

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

Total Hydrocarbon Content (% w/w) = 4.54

4. First Aid Measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

Eye Exposure: Flush immediately with water for at least 15 minutes.

Contact physician if symptoms persist.

Skin Exposure: Remove contaminated clothes. Wash thoroughly with water (and soap).

Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable Do not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable



SDS v1 GHS / OSHA

Revised Date: 2023-04-18 00:00

Product: Crafter's Choice™ Wood - 100% Upcycled Fragrance Oil

Page 5 of 8 Print Date: 2023-04-27

Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

7820 E Pleasant Valley Road

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

8. Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits:

ComponentACGIHACGIHOSHAOSHATWA ppmSTEL ppmTWA ppmSTEL ppm

80-56-8 *pinene* 20

Engineering Controls: Use local exhaust as needed.
8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure

Respiratory protection: Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid

Odor: Conforms to Standard

Color: Pale Yellow (G2) - Yellow (G4)

Viscosity: Liquid

Freezing Point:

Boiling Point:

Not determined

Melting Point:

Not determined

Not determined

Flashpoint (CCCFP):

Auto flammability:

Explosive Properties:

None Expected

Oxidizing properties:

None Expected

 Vapor Pressure (mmHg@20 C):
 0.0786

 %VOC:
 4.99

 Specific Gravity @ 25 C:
 0.9350



Revised Date: 2023-04-18 00:00

SDS v1 GHS / OSHA

Product: Crafter's Choice™ Wood - 100% Upcycled Fragrance Oil

Page 6 of 8 Print Date: 2023-04-27

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com

Soluble in:

Density (g/mL) @ 25 C: 0.9320

Refractive Index @ 20 C: 1.4593

10. Stability and Reactivity

10.1 ReactivityNone10.2 Chemical stabilityStable

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

Oil

10.5 Incompatible materials Strong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition products None known

11. Toxicological Information

11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 4284.1782) May be harmful if swallowed

Acute toxicity - Dermal - (Rabbit) mg/kg (LD50: 3970.5201) May be harmful in contact with skin

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LD50: 55.5156) May be harmful if inhaled

Skin corrosion / irritation Causes skin irritation

Serious eye damage / irritation Causes serious eye damage

Respiratory sensitization Not classified - the classification criteria are not met

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Suspected of damaging fertility or the unborn child

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

12. Ecological Information

12.1 Toxicity

Acute acquatic toxicity Toxic to aquatic life

Chronic acquatic toxicity Harmful to aquatic life with long lasting effects

Toxicity Data on soilno data availableToxicity on other organismsno data available

12.2 Persistence and degradability

no data available



Revised Date: 2023-04-18 00:00

SDS v1 GHS / OSHA

Page 7 of 8

Print Date: 2023-04-27

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944 www.WholesaleSuppliesPlus.com Product: Crafter's ChoiceTM Wood -100% Upcycled Fragrance Oil

12.3 Bioaccumulative potential no data available 12.4 Mobility in soil no data available 12.5 Other adverse effects no data available

13. **Disposal Conditions**

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

Marine Pollutant Nο

Regulator UN-nr. Class **Pack Group** Sub Risk

U.S. DOT (Non-Bulk) Not Regulated - Not Dangerous Goods

Chemicals NOI

ADR/RID (International Road/Rail) Not Regulated - Not Dangerous Goods

Chemicals NOI

Not Regulated - Not Dangerous Goods IATA (Air Cargo)

Chemicals NOI

IMDG (Sea) Not Regulated - Not Dangerous Goods

Chemicals NOI

15. Regulatory Information

U.S. Federal Regulations

TSCA (Toxic Substance Control Act) All components of the substance/mixture are listed or exempt

40 CFR(EPCRA, SARA, CERCLA and CAA) This product contains NO components of concern.

U.S. State Regulations

California Proposition 65 Warning This product contains the following components:

123-35-3(NF 204-622-5 0.01 - 0.1% beta-Myrcene (Natural Source)

140-67-0 205-427-8 <= 2 ppm Estragole (Methyl chavicol) (Natural Source)

89-82-7 201-943-2 <= 1 ppm Pulegone (Natural Source)

Canadian Regulations

DSL 100.00% of the components are listed or exempt.

16. Other Information

GHS H-Statements referred to under section 3 and not listed in section 2

H302: Harmful if swallowed H226: Flammable liquid and vapour H304: May be fatal if swallowed and enters airways H316: Causes mild skin irritation H317: May cause an allergic skin reaction H319: Causes serious eye irritation



100% Upcycled Fragrance Oil

Product:

Crafter's Choice™ Wood -

Revised Date: 2023-04-18 00:00

Page 8 of 8

Print Date: 2023-04-27

SDS v1 GHS / OSHA

7820 E Pleasant Valley Road Independence, OH 44131 (800) 359-0944

(800) 359-0944 www.WholesaleSuppliesPlus.com

H335: May cause respiratory irritation

H402: Harmful to aquatic life

H411: Toxic to aquatic life with long lasting effects

Total Fractional Values

H320: Causes eye irritation

H400: Very Toxic to aquatic life

(TFV) Risk

(90.06) Acute Toxicity Inhalation, Category 5

H410: Very toxic to aquatic life with long lasting effects

(52.50) Sensitization, Skin, Category 1A

(10.04) Sensitization, Skin, Category 1B

(6.13) Skin Corrosion/Irritation, Category 3

(3.44) Eye Damage/Eye Irritation, Category 1

(1.86) Reproductive Toxicity, Category 2

(1.17) Acute Toxicity Oral, Category 5

(TFV) Risk

(52.50) Sensitization, Skin, Category 1

(15.94) Eye Damage/Eye Irritation, Category 2A

(7.60) Aquatic Chronic Toxicity, Category 3

(6.10) Skin Corrosion/Irritation, Category 2

(3.10) Aquatic Acute Toxicity, Category 2

(1.26) Acute Toxicity Dermal, Category 5

(1.04) Aquatic Chronic Toxicity, Category 4

Department issuing data sheet:

Department E-mail address:

Remarks

This safety data sheet is based on the properties of the material known to IndiMade Brands, LLC at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment IndiMade Brands, LLC holds no responsibility. This document is not intended for quality assurance purposes.