SDS v1 GHS / OSHA

Product: Mahogany Teakwood Slatkin Type

Page 1 of 7

Print Date: 2020-03-31 09:45

Revised Date: 2019-08-01 00:00

# I. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade Name:** Mahogany Teakwood Slatkin Type

### 1.2 Relevant indentified product use

**Intended use:** Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the safety data sheet

#### 1.4 Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International

# 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

#### Classification according to GHS

Acute Toxicity Oral, Category 4 H302: Harmful if swallowed

Acute Toxicity Dermal, Category 5 H313 : May be harmful in contact with skin Sensitization, Skin, Category 1B H317 : May cause an allergic skin reaction

Acute Toxicity Inhalation, Category 5 H333 : May be harmful if inhaled Aquatic Acute Toxicity, Category 1 H400 : Very Toxic to aquatic life

Aquatic Chronic Toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects

#### Classification OSHA (Provisions 1910.1200 of title 29)

Acute Toxicity Oral, Category 4 H302: Harmful if swallowed

Sensitization, Skin, Category 1B H317 : May cause an allergic skin reaction

Aquatic Acute Toxicity, Category 1 H400 : Very Toxic to aquatic life

#### **Classification Other**

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater,

by the following: None [X] ACGIH [] IARC [] NTP [] OSHA []

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

#### Hazard pictograms





Signal Word: Warning

SDS v1 GHS / OSHA

# **Safety Data Sheet**

Product: Mahogany Teakwood Slatkin Type

Page 2 of 7

Print Date: 2020-03-31 09:45

Revised Date: 2019-08-01 00:00

# **Hazard statments**

H302	Harmful if swallowed
H313	May be harmful in contact with skin
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H400	Very Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

# **Precautionary Statements**

#### Prevention:

P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P273	Avoid release to the environment

#### Response:

P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth
P302 + P352	IF ON SKIN: Wash with soap and water
P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
P333 + P313	If skin irritation or a rash occurs: Get medical advice/attention
P363	Wash contaminated clothing before reuse
P391	Collect Spillage

#### 2.3 Other Hazards

no data available

# 3. Composition/Information on Ingredients

# 3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

CAS# Ingredient	EC#	Conc. Range	GHS Classification		
<b>120-51-4</b> <i>Benzyl Be</i>	204-402-9 enzoate	> 80 %	H302; H313; H400; H411		
118-58-1	204-262-9	5 - 10 %	H303; H317; H320; H401; H412		
Benzyl Salicylate					
101-86-0	202-983-3	2 - 5 %	H303; H316; H317; H400; H411		
Hexyl cinnamal					
32388-55-9	251-020-3	1 - 2 %	H303; H317; H400; H410		
Acetyl cedrene					
67634-15-5	266-819-2	1 - 2 %	H315; H317; H400; H411		
Ethyl 2,2-dimethylhydrocinnamal					

SDS v1 GHS / OSHA

Revised Date: 2019-08-01 00:00

Product: Mahogany Teakwood Slatkin Type

Page 3 of 7

Print Date: 2020-03-31 09:45

CAS# Conc.
Ingredient EC# Range GHS Classification

**80-54-6** 201-289-8 0.1 - 1.0 % H227; H302; H315; H317; H361; H401;

Butylphenyl Methylpropional H412

**1205-17-0** 214-881-6 0.1 - 1.0 % H303; H317; H361; H401; H411

a-Methyl-1,3-benzodioxole-5-propionaldehyde

See Section 16 for full text of GHS classification codes

See Section 16 for full text of GHS classification codes which where not shown in section 2

Total Hydrocarbon Content (% w/w) = 0.09

# 4. First Aid Measures

4.1 Description of first aid measures

**Inhalation:** Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

**Eye Exposure:** Flush immediately with water for at least 15 minutes.

Contact physician if symptoms persist.

**Skin Exposure:** Remove contaminated clothes. Wash thoroughly with water (and soap).

Contact physician if symptoms persist.

**Ingestion:** Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms:** no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable Do not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

**During fire fighting:** Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

### 6. Accidental Release Measures

# 6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

#### 6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

SDS v1 GHS / OSHA

Revised Date: 2019-08-01 00:00

Product: Mahogany Teakwood Slatkin Type

Page 4 of 7

Print Date: 2020-03-31 09:45

# 6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

#### 6.4 Reference to other sections

Not Applicable

# 7. Handling and Storage

#### 7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid uncoated metal container. Keep air contact to a minimum.

#### 7.3 Specific end uses

No information available

# 8. Exposure Controls/Personal Protection

#### 8.1 Control parameters

**Exposure Limits:** Contains no substances with occupational exposure limit values.

Engineering Controls: Use local exhaust as needed.
8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure

**Respiratory protection:** Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

**Skin protection:** Avoid Skin contact. Use chemically resistant gloves as needed.

# 9. Physical and Chemical Properties

# 9.1 Information on basic physical and chemical properties

Appearance: Liquid

Odor: Conforms to Standard

**Color:** Yellow Tint to Pale Yellow (G0/1-2)

Viscosity: Liquid

Freezing Point:

Boiling Point:

Not determined

Not determined

Not determined

Not determined

Not determined

Flashpoint (CCCFP):

>200 F (93.33 C)

Auto flammability:

Not determined

Explosive Properties:

None Expected

Product: Mahogany Teakwood Slatkin Type

Revised Date: 2019-08-01 00:00

SDS v1 GHS / OSHA

Page 5 of 7

Print Date: 2020-03-31 09:45

Oxidizing properties: None Expected

 Vapor Pressure (mmHg@20 C):
 0.0055

 %VOC:
 0.28

 Specific Gravity @ 25 C:
 1.1000

 Density @ 25 C:
 1.0970

 Refractive Index @ 20 C:
 1.5590

 Soluble in:
 Oil

# 10. Stability and Reactivity

10.1 Reactivity None10.2 Chemical stability Stable

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

**10.5 Incompatible materials** Strong oxidizing agents, strong acids, and alkalis

**10.6 Hazardous decomposition products** None known

### 11. Toxicological Information

# 11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 1613.9429) Harmful if swallowed

Acute toxicity - Dermal - (Rabbit) mg/kg (LD50: 4125.6458) May be harmful in contact with skin

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LD50: 241.6614) May be harmful if inhaled

Skin corrosion / irritationNot classified - the classification criteria are not metSerious eye damage / irritationNot classified - the classification criteria are not metRespiratory sensitizationNot classified - the classification criteria are not met

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

SDS v1 GHS / OSHA

Revised Date: 2019-08-01 00:00

Product: Mahogany Teakwood Slatkin Type

Page 6 of 7

Print Date: 2020-03-31 09:45

# 12. Ecological Information

### 12.1 Toxicity

Acute acquatic toxicity

Very Toxic to aquatic life

Chronic acquatic toxicity

Toxic to aquatic life with long lasting effects

Toxicity Data on soilno data availableToxicity on other organismsno data available

12.2 Persistence and degradabilityno data available12.3 Bioaccumulative potentialno data available12.4 Mobility in soilno data available12.5 Other adverse effectsno data available

# 13. Disposal Conditions

#### 13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

# 14. Transport Information

Marine Pollutant Yes. Ingredient of greatest environmental impact :

120-51-4: (> 80 %): Benzyl Benzoate

Regulator	Class	Pack Group	Sub Risk	UN-nr.
U.S. DOT (Non-Bulk)	Not Regulated - Not Dangerous Goods			
Chemicals NOI				
ADR/RID (International Road/Rail)				
Environmentally Hazardous Substance, Liquid, n.o.s.	9	III		UN3082
IATA (Air Cargo)				
Environmentally Hazardous Substance, Liquid, n.o.s.	9	III		UN3082
IMDG (Sea)				
Environmentally Hazardous Substance, Liquid, n.o.s.	9	III		UN3082

# 15. Regulatory Information

#### **U.S. Federal Regulations**

TSCA (Toxic Substance Control Act)

All components of the substance/mixture are listed or exempt

**40 CFR(EPCRA, SARA, CERCLA and CAA)** This product contains NO components of concern.

**U.S. State Regulations** 

California Proposition 65 Warning

This product contains the following components:

# SDS v1 GHS / OSHA

# **Safety Data Sheet**

Product: Mahogany Teakwood Slatkin Type

Page 7 of 7

Print Date: 2020-03-31 09:45

Revised Date: 2019-08-01 00:00

140-67-0 205-427-8 0.01 - 0.1% Estragole (Methyl chavicol) (Natural Source)

94-59-7 202-345-4 <= 4 ppm Safrole (Natural Source)

93-15-2 202-223-0 <= 2 ppm Methyl Eugenol (Natural Source)

### **Canadian Regulations**

**DSL** 100.00% of the components are listed or exempt.

# 16. Other Information

#### GHS H-Statements referred to under section 3 and not listed in section 2

H227 : Combustible liquid
H303 : May be harmful if swallowed
H315 : Causes skin irritation
H317 : May cause an allergic skin reaction
H361 : Suspected of damaging fertility or the unborn child
H401 : Toxic to aquatic life

H410 : Very toxic to aquatic life with long lasting effects

H412 : Harmful to aquatic life with long lasting effects

#### **Total Fractional Values**

(TFV) Risk
(45.96) Aquatic Chronic Toxicity, Category 3
(7.00) Sensitization, Skin, Category 1B
(3.84) Aquatic Chronic Toxicity, Category 4
(1.24) Acute Toxicity Oral, Category 4
(1.25) Risk
(20.69) Acute Toxicity Inhalation, Category 5
(4.56) Aquatic Chronic Toxicity, Category 2
(3.47) Aquatic Acute Toxicity, Category 1
(1.21) Acute Toxicity Dermal, Category 5

#### Remarks

This safety data sheet is based on the properties of the material known at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment Just Scent holds no responsibility. This document is not intended for quality assurance purposes.