Product: **Melt Down**

> Page 1 of 7 2019-09-04

SDS Type: GHS / OSHA

Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

Trade Name: Melt Down

1.2 Relevant indentified product use

Intended use: Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the safety data sheet

Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International

2. **Hazards Identification**

Acute Inhalation

Classification of the substance or mixture 2.1

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS and (EC) No 1272/2008 (CLP)

Flammable Liquids, Category 4 H227: Combustible liquid

Acute Toxicity Oral, Category 5 H303: May be harmful if swallowed

H313: May be harmful in contact with skin Acute Toxicity Dermal, Category 5

Skin Corrosion/Irritation, Category 2 H315: Causes skin irritation

Sensitization, Skin, Category 1B H317: May cause an allergic skin reaction

Acute Toxicity Inhalation, Category 5 H333: May be harmful if inhaled Aquatic Acute Toxicity, Category 1 H400: Very Toxic to aquatic life

H411: Toxic to aquatic life with long lasting effects Aquatic Chronic Toxicity, Category 2

Classification OSHA (Provisions 1910.1200 of title 29)

Flammability Class IIIA Combustible Liquid

12: Causes moderate skin irritation. Acute Dermal/Eye

16: Causes eye irritation.

9: Harmful if absorbed through the skin. 24: Causes respiratory tract irritation.

25: Inhalation at high levels may cause: headache.

Acute Oral 2: Harmful if swallowed

Genotoxicity 36: Suspected of causing genetic defects Sensitization/Allergic Response 31: May cause allergic skin reaction.

Target Organ Effects 26: Prolonged or repeated ingestion may cause damage to: kidneys, liver, spleen,

blood, brain, bile duct, salivary gland.

27: Prolonged or repeated inhalation may cause damage to: nasal mucosa.

28: Prolonged or repeated Dermal Exposure may cause damage to: kidneys, skin

Product: **Melt Down**

> Page 2 of 7 2019-09-04

SDS Type: GHS / OSHA

Carcinogenicity

This mixture contains ingredients identified as carcinogens, at 0.1% or greater, by the following:None [X] ACGIH [] IARC [] NTP [] OSHA []

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal Word: Warning

Hazard statments

H227	Combustible liquid
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H400	Very Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention:

P264 Wash hands thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

Response:

P302 + P352 IF ON SKIN: Wash with soap and water

P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell

P312 Call a POISON CENTER or doctor/physician if you feel unwell P333 + P313 If skin irritation or a rash occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse

P363 Wash contaminated clothing before reuse

P370 + P378 In case of fire: Use Carbon dioxide (CO2), Dry chemical, or Foam for extinction. Do not use

a direct water jet on burning material

P391 Collect Spillage

2.3 Other Hazards

no data available

3. Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

Product: Melt Down

Page 3 of 7 2019-09-04

SDS Type: GHS / OSHA

CAS# Ingredient	EC#	Conc. Range	GHS Classification	OSHA Classification
120-51-4	204-402-9	20 - 30 %	H302; H313; H400; H411	28, 3
Benzyl Be		0 50/	11007, 11000, 11045, 11047, 11400	00 0 00
14073-97-3 <i>I-Menthor</i>	237-926-1 ne	2 - 5 %	H227; H303; H315; H317; H402	26, 3, 36
470-82-6	207-431-5	2 - 5 %	H226; H303; H316; H317	26, 27, 3
Eucalypto	ol .			
5989-27-5	227-813-5	2 - 5 %	H226; H304; H315; H317; H400; H410	11, 15, 23
Limonene	9			
121-32-4	204-464-7	2 - 5 %	H303; H320; H402	
Ethyl van	illin			
15356-70-4	239-388-3	1 - 2 %	H227; H303; H315; H320; H402	
Menthol				
127-91-3	204-872-5	1 - 2 %	H226; H304; H315; H317; H400; H410	11, 15, 24, 25, 31
ß-Pinene				
91-64-5	202-086-7	1 - 2 %	H302; H317; H402	12, 15, 2, 26, 31, 9
Coumarin)			
1843-05-6	217-421-2	0.1 - 1.0 %	H317	
Methanor	ne, [2-hydroxy-4	-(octyloxy)pheny	l]phenyl-	
		GHS classification		

4. First Aid Measures

4.1 Description of first aid measures

Total Hydrocarbon Content (% w/w) = 7.64

Inhalation: Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

Eye Exposure: Flush immediately with water for at least 15 minutes.

Contact physician if symptoms persist.

Skin Exposure: Remove contaminated clothes. Wash thoroughly with water (and soap).

Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable Do not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

Product: Melt Down

Page 4 of 7 2019-09-04

SDS Type: GHS / OSHA

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid plastic and uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

8. Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits:

 Component
 ACGIH
 ACGIH
 OSHA
 OSHA

 TWA ppm
 STEL ppm
 TWA ppm
 STEL ppm

127-91-3 *β-Pinene* 20

Engineering Controls: Use local exhaust as needed.

8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure

Respiratory protection: Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

Product: Melt Down

Page 5 of 7 2019-09-04

SDS Type: GHS / OSHA

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid

Odor: Conforms to Standard Color: Conforms to Standard

Viscosity: Liquid

Freezing Point:

Boiling Point:

Not determined

Melting Point:

Not determined

Not determined

Flashpoint (CCCFP):

Auto flammability:

Not determined

Explosive Properties:

None Expected

Oxidizing properties:

Vapor Pressure (mmHg@20 C): 0.0236 **%VOC:** 17.3

Specific Gravity @ 25 C: Not determined

Density @ 25 C: Not determined

Refractive Index @ 20 C: Not determined

Soluble in: Oil

10. Stability and Reactivity

10.1 ReactivityNone10.2 Chemical stabilityStable

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

10.5 Incompatible materials Strong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition productsNone known

11. Toxicological Information

11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 2,809.50) May be harmful if swallowed

Acute toxicity - Dermal - (Rabbit) mg/kg (LD50: 4,572.22) May be harmful in contact with skin

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LC50: 166.45) May be harmful if inhaled

Skin corrosion / irritation Causes skin irritation

Serious eye damage / irritation

Not classified - the classification criteria are not met

Respiratory sensitization

Not classified - the classification criteria are not met

Product: Melt Down

Page 6 of 7 2019-09-04

SDS Type: GHS / OSHA

Skin sensitizationMay cause an allergic skin reactionGerm cell mutagenicityNot classified - the classification criteria are not metCarcinogenicityNot classified - the classification criteria are not metReproductive toxicityNot classified - the classification criteria are not metSpecific target organ toxicity - single exposureNot classified - the classification criteria are not metSpecific target organ toxicity - repeated exposureNot classified - the classification criteria are not metAspiration hazardNot classified - the classification criteria are not met

12. Ecological Information

12.1 Toxicity

Acute aquatic toxicity Very Toxic to aquatic life

Chronic aquatic toxicity

Toxic to aquatic life with long lasting effects

Toxicity Data on soilno data availableToxicity on other organismsno data available

12.2 Persistence and degradabilityno data available12.3 Bioaccumulative potentialno data available12.4 Mobility in soilno data available12.5 Other adverse effectsno data available

13. Disposal Conditions

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

Regulator		Class	Pack Group	Sub Risk	UN-nr.		
U.S. DOT (Non-Bulk)		Not Regulated	Not Regulated - Not Dangerous Goods				
Chemicals NOI							
ADR/RID (International Road/Rail)							
Environmentally Hazardous Liquid, n.o.s.	Substance,	9	III		UN3082		
IATA (Air Cargo)							
Environmentally Hazardous Liquid, n.o.s.	Substance,	9	III		UN3082		
IMDG (Sea)							
Environmentally Hazardous Liquid, n.o.s.	Substance,	9	III		UN3082		

Product: Melt Down

Page 7 of 7 2019-09-04

SDS Type: GHS / OSHA

15. Regulatory Information

U.S. Federal Regulations:

TSCA (Toxic Substance Control Act): All components of the substance/mixture are listed or exempt

40 CFR(EPCRA, SARA, CERCLA and CAA) This product contains NO components of concern.

U.S. State Regulations:

California Proposition 65 Warning

This product contains the following components:

89-82-7 201-943-2 0.01 - 0.1% Pulegone (Natural Source) 123-35-3(NF 204-622-5 0.1 - 1.0 % beta-Myrcene (Natural Source)

Canadian Regulations:

DSL / NDSL 100.00% of the components are listed or exempt.

16. Other Information

GHS H-Statements referred to under section 3

H226 : Flammable liquid and vapour
H302 : Harmful if swallowed
H304 : May be fatal if swallowed and enters airways
H316 : Causes mild skin irritation
H317 : May cause an allergic skin reaction
H320 : Causes eye irritation

H402 : Harmful to aquatic life H410 : Very toxic to aquatic life with long lasting effects

Total Fractional Values

(TFV) Risk (TFV) Risk

(1.38) Skin Corrosion/Irritation, Category 2 (3.70) Sensitization, Skin, Category 1B (1.03) Aquatic Acute Toxicity, Category 1 (2.77) Aquatic Chronic Toxicity, Category 2

Remarks

This safety data sheet is based on the properties of the material known at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment Just Scent holds no responsibility. This document is not intended for quality assurance purposes.